

**652402800**
**VELLUM EXTRA -R400- YG\_D**
**652402800**

<b>Face</b>	A white, surface-sized, calendered woodfree printing paper with smooth surface.
<b>Adhesive</b>	Acrylic based, removable adhesive for general use with long term removability.
<b>Liner</b>	Yellow, supercalendered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system.

<b>Face</b>	<b>Method</b>	<b>Unit</b>	<b>Target</b>	
Basis Weight	ISO 536	g/m <sup>2</sup>	70 ± 3	
Thickness	ISO 534	µm	67 ± 3	
<b>Adhesive</b>				
Peel adhesion 90°	FTM 2 st.st	N/m	min. 40	(min. 1 N/25mm)
Loop Tack	FTM 9 glass	N/m	min. 150	(min. 3,75 N/25mm)
Min. appl temperature		°C	0	
Service temperature		°C	-20 / +80	
<b>Liner</b>				
Basis Weight	ISO 536	g/m <sup>2</sup>	60 ± 2	
Thickness	ISO 534	µm	51 ± 3	
Transparency	DIN 53147	%	49	
<b>Laminate</b>				
Thickness	ISO 534	µm	130 ± 5	

**Application and use**

The product is suitable for removable labels for stores and supermarkets, process labelling applications and industrial labelling.

**Conversion and Printing**

Surface is suitable for excellent printing quality by all conventional print technologies and thermal transfer printing.

**Packaging**

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

**Shelf Life and Storage Conditions**

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.