

**654102657**
**PP WHITE 60 TC-WS820-W.Kraft 80\_D**

<b>Face</b>	A white pearlescent, topcoated polypropylene film with high brilliance and internal reflectivity.
<b>Adhesive</b>	Acrylic based, permanent, non-bleeding adhesive with improved water resistance, good clarity, UV resistance and short-term removability.
<b>Liner</b>	White, woodfree kraft backing paper for optimal layflat performance. Specially designed for laminate where thin backing is needed.

<b>Face</b>	<b>Method</b>	<b>Unit</b>	<b>Target</b>
Basis Weight	ISO 536	g/m <sup>2</sup>	42 ± 2
Thickness	ISO 534	µm	60 ± 3
<b>Adhesive</b>			
Peel adhesion 90°	FTM 2 st.st	N/m	min.200 (min. 5 N/25mm)
Loop Tack	FTM 9 glass	N/m	min.400 (min. 10 N/25mm)
Min. appl. temperature		°C	+5
Service temperature		°C	-20 / +100
<b>Liner</b>			
Basis Weight	ISO 536	g/m <sup>2</sup>	80 ± 3
Thickness	ISO 534	µm	82 ± 5
<b>Laminate</b>			
Thickness	ISO 534	µm	152 ± 5

### Application and use

For use in labelling of quality products such as luxury items, cosmetics, toiletries and household chemicals requiring durability and resistance to chemicals or moisture, where a backing with high strength or that will undergo sheeting is required.

### Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

### Conversion and Printing

Topcoated surface is suitable for printing by the usual printing technologies including letterpress, flexo, gravure and screen printing.

### Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.

All information and recommendations about Frimpeks products are based on our existing knowledge and experiences but do not mean a guarantee or warranty. As the products are used for different applications we recommend checking suitability of product prior to use. All information is subject to change without notice. End user obliged and verifies the above information before using the material.