

654153745
PP MATT WHITE 65 TC -WS745- WG_D

Face	A white matt, polypropylene film with high opacity, whiteness and good printability.
Adhesive	Acrylic based permanent adhesive for special use. Designed for special purpose applications with excellent performance on a variety of surfaces such as plastic bottles for oil and cosmetic product.
Liner	White, supercalandered siliconised glassine paper. Specially designed for high speed conversion, punching and perforation. Transparency allows its use in automatic dispensing system.

Face	Method	Unit	Target	
Basis Weight	ISO 536	g/m ²	47 ± 3	
Thickness	ISO 534	µm	65 ± 5	
Adhesive				
Peel adhesion 90°	FTM 2 st.st	N/m	min.440	(min. 11 N/25mm)
Loop Tack	FTM 9 glass	N/m	min.700	(min. 17,5 N/25mm)
Min. appl temperature		°C	+5	
Service temperature		°C	-20 / +80	
Liner				
Basis Weight	ISO 536	g/m ²	60 ± 2	
Thickness	ISO 534	µm	51 ± 3	
Transparency	DIN 53147	%	51	
Laminate				
Thickness	ISO 534	µm	130 ± 5	

Application and use

For use in labelling of quality products such as luxury items, cosmetics, toiletries and household chemicals requiring durability and resistance to chemicals or moisture.

Conversion and Printing

Topcoated surface is suitable for printing by the usual printing technologies including letterpress, flexo, gravure and screen printing.

Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.