

651001350
COPYLASER -PE300- W.KRAFT 55_D

Face	Matt, white, woodfree machine finished paper with good opacity. This paper is suitable for multifunctional information labelling, especially designed for ink jet, lasers and photocopiers.
Adhesive	Acrylic based, strong permanent adhesive for general use. This adhesive gives excellent initial tack and adhesion even on a wide variety substrates including apolar, rough and curved substrates. Edge bleeding may occur.
Liner	White, woodfree kraft backing paper for optimal layflat performance. Specially designed for laminate where thin backing is needed.

Face	Method	Unit	Target	
Basis Weight	ISO 536	g/m ²	70 ± 3	
Thickness	ISO 534	µm	90 ± 4	
Adhesive				
Peel adhesion 90°	FTM 2 st.st	N/m	min.275	(min. 6,875 N/25mm)
Loop Tack	FTM 9 glass	N/m	min.550	(min. 13,75 N/25mm)
Min. appl temperature		°C	+5	
Service temperature		°C	-20 / +80	
Liner				
Basis Weight	ISO 536	g/m ²	45 ± 2	
Thickness	ISO 534	µm	47 ± 3	
Laminate				
Thickness	ISO 534	µm	150 ± 5	

Application and use

This product is designed for the manufacture of A4 sheets for use in multifunctional information labelling at laser printers, copiers and inkjet printers. It is ideal for office use and information labelling such as address, instruction. The product has tight release property to avoid predispensing during printing or copying process.

Conversion and Printing

The material can be converted by the conventional roll-to-sheet conversion technologies.

Packaging

The rolls are sliced according to customer requirements, double sided siliconised papers are put between of rolls. Paperboards are placed at the sides. They are delivered on pallets. Product description labels are fixed on rolls.

Shelf Life and Storage Conditions

Two years when stored away from direct sunlight and heat, in a dark, dry place at a temperature of 22 °C ± 2 °C with a relative humidity of 50 %, ± 5%.